

## Challenge:

Good communication throughout a busy factory is challenging, but critical to maintaining a steady workflow that optimizes productivity: supervisors providing direction to workers, employees needing additional parts, requests for maintenance or assistance. Banner's wireless Direct Select™ provides two-way communication in a battery powered, completely autonomous device. It combines a multicolored indicator with capacitive touch input, a numerical display, and four tactile push buttons.

## Banner Wireless Value:

- **Simple & Powerful:** Numerical display, multicolored indicator, and capacitive touch provide multiple methods for two-way communication that increases productivity.
- **Deploy Easily:** Simplify installation on existing equipment and remote locations where a wired solution is impractical.
- **Peel & stick:** Battery powered with no wiring needed.
- **Two-way communication:** Node can send information back to the controller for short or missing items.
- **Multi-colored indication:** Active control for more than one operator or product using different colors.
- **Flexible interface:** Enable increment/decrement as well as other commands.
- **Compatibility:** Use the numerical LCD to display status from other Banner sensors & nodes (e.g., temperature, tank level)



## Banner Wireless Direct Select™ Node

Improve efficiency with better communication

- ✓ Operator interaction anywhere in a facility
- ✓ Reduce mistakes by directing operators where to go
- ✓ Ideal for mobile applications
- ✓ Capable of up to 8 colors
- ✓ 0 – 999 numerical display
- ✓ Up to two-year battery life
- ✓ DIP switch configurable



## Key Applications

- Call for parts/service/pickup
- Pick to light
- Mobile equipment
- Operator guidance
- Put to light

## Direct Select™ Node Models

Model Number	DXM Gateway	Additional Notes
DX80N9DSTS	900MHz	Multi-colored capacitive touch/indicator with four buttons and a 3-digit numerical LCD.
DX80N9DSTS-NB	900MHz Battery Sold Separately	