

K50 and K30 Pro



Bolder Indication for Everyone, Anywhere

- Simplified ordering and design
- Reliable performance in harsh environments
- Improved production efficiency
- Compact models for low profile applications
- Full flexibility of colors and animations with Pro Editor software or IO-Link®



Give Your Equipment a Voice




30 or 50 mm dome
or 50 mm compact



Food grade materials



Audible options
(50 mm models only)



Avoid nuisance maintenance and replacement expense



Hear status information directly



Rely on performance in washdown and humid environments



Customize device configuration with advanced color and animation options



Select compliant models for use in food and beverage processing



Simplify ordering, stock and spare parts with flexible, customizable units



Bolder Indication for Everyone, Anywhere



14 colors now available
in one housing

- Get seven colors via only three inputs
- Save controller outputs and wiring
- Improve production efficiency through enhanced visual management
- Install wherever you need indication to improve communication and productivity
- Standardize to simplify ordering and spare parts
- Collaborate with Banner on custom models
- Enhance troubleshooting and branding with colors dynamically using IO-Link models
- Create your own custom units with Pro Editor software or IO-Link
- K50 compact models are available for low profile applications



- Factory calibrated color points
- Bright, 360° visibility
- Impact-resistant polycarbonate material
- IP66/67/69K, NEMA/UL Type 4X, 13
- Bimodal discrete inputs, plus flashing input
- Standard base dimensions and connector options




Visit www.bannerengineering.com/proeditor
for full details on the Pro Editor software

IO-Link®




Limitless Capabilities with IO-Link

- Universal connection
- Millions of color options
- Intensity control
- Animation options
- Drop-in installation
- Simplified wiring



K50L2 Pro

Example Model Number: K50L2RGB7Q




* Audible models not available in FDA-grade material or compact
 ** Compact and integral QD models not available in FDA-grade material



K30L2 Pro

Example Model Number: K30L2RGB7Q



* Integral QD and Terminal Screw models not available in FDA-grade material

QD models require mating cordset

Power	RGB7: 10 to 30 V dc; 220 mA Max. at 10 V dc; 100 mA Max. at 30 V dc RGBK: 24 V dc ±25%; 115 mA typical at 24 V dc; 150 mA Max. at 18 V dc
Operating Conditions	-40 to 50 °C
Construction	Standard models: Polycarbonate FDA models: Copolyester
Environmental Rating	K50L2: Standard: IEC IP66/IP67/IP69K Standard Audible: IEC IP50 Sealed Audible: IEC IP66/IP67/IP69K K50CL2: IEC IP66/IP67/IP69K K30L2: IEC IP66/IP67/IP69K
Certifications	CE UL LISTED

Accessories



PRO-KIT-ACC Includes:

MQDC-506-USB
Pro Converter Cable
CSBM1251FM1251M
Splitter
PSW-24-1
Power Supply

ACC-PRO-CABLES
Mating accessory for
cabled and terminal
models
MQDC-801-5M-PRO
5-pin to 8-pin
double-ended cordset



PRO-KIT-K50 Includes: PRO-KIT plus
K50L2RGB7Q Pro Series-enabled K50

PRO-KIT Includes:
MQDC-506-USB
Pro Converter Cable
CSBM1251FM1251M
Splitter
PSW-24-1
Power Supply



M12/Euro-Style Cordsets
Straight connector models
listed; for right-angle, add
RA to the end of the model
(example, MQDC1-506RA)

4-Pin	5-Pin
MQDEC-406 2 m (6.5')	MQDC1-506 2 m (6.5')
MQDEC-415 5 m (15')	MQDC1-515 5 m (15')
MQDEC-430 9 m (30')	MQDC1-530 9 m (30')



M12/ Euro-Style
Washdown Cordset (IP69K)
Straight connector models

5-Pin
MQDC-WDSS-0506 2 m (6.5')
MQDC-WDSS-0515 5 m (15')
MQDC-WDSS-0530 9 m (30')

NOTE: IO-LINK models require double-ended cordset



PN 172048 rev. B

© 2019 Banner Engineering Corp. Minneapolis, MN USA

1-888-373-6767

www.bannerengineering.com

