

PFH-T

COMPACT FAN HEATER

200 W - 1200 W

FLEXIBLE MOUNTING OPTIONS

Unit can be direct mounted or connected to standard DIN rail **without tools** using the included snap fastener.

PTC HEATER TECHNOLOGY

Uses a self regulating heating element designed to prevent overheating and safe operation within your application.

COMPACT DESIGN

Wide range for heat options from 200W to 1200W all housed in the same compact housing.

INTEGRATED THERMOSTAT

Built in thermostat allows our heater to be set to the precise temperature required for your application.

TOUCH-SAFE OUTER HOUSING

Well insulated ABS high-temperature resistant plastic housing material ensures that unit remains cool and safe to touch during operation.

UL CERTIFIED

Heaters are UL Recognized to NITW2 and NITW8 standards allowing for easy integration into UL 508A panels.

INTEGRATED FAN

Compact fan moves air across the heater elements to provide quick and efficient heating of the enclosure.

QUICK CONNECTS

Wires too long, too short or wrong color? Save time and money when installing or moving the unit with our UL listed quick connects.



PFH-T

COMPACT FAN HEATER

200W-1200W

Pfannenbergs PFH-T Compact Fan Heater is perfect for maintaining precise temperatures required for the proper function of electronics while also protecting equipment from damaging condensation caused by changes in temperature or humidity.

Model	Part No.	Heating Performance*	Power Consumption	Airflow Volume	Starting current	Width	Length	Height	Weight
		W	W	CFM (m3/h)	A	in (mm)	in (mm)	in (mm)	lb (kg)
PFH-T 200 (115 V)	170 2071 5034	200	215	30 (50)	9	3.46 (88)	5.24 (133)	5.59 (142)	1.6 (.74)
PFH-T 200 (230 V)	170 2071 0034	200	215	30 (50)	9	3.46 (88)	5.24 (133)	5.59 (142)	1.6 (.74)
PFH-T 400 (115 V)	170 4071 5034	400	415	30 (50)	15	3.46 (88)	5.24 (133)	5.59 (142)	1.6 (.74)
PFH-T 400 (230 V)	170 4071 0034	400	415	30 (50)	15	3.46 (88)	5.24 (133)	5.59 (142)	1.6 (.74)
PFH-T 650 (115 V)	170 6571 5034	650	665	30 (50)	20	3.46 (88)	5.24 (133)	5.59 (142)	1.6 (.74)
PFH-T 650 (230 V)	170 6571 0034	650	665	30 (50)	20	3.46 (88)	5.24 (133)	5.59 (142)	1.6 (.74)
PFH-T 800 (115 V)	170 8071 5034	800	815	30 (50)	31	3.46 (88)	5.24 (133)	5.59 (142)	1.6 (.74)
PFH-T 800 (230 V)	170 8071 0034	800	815	30 (50)	31	3.46 (88)	5.24 (133)	5.59 (142)	1.6 (.74)
PFH-T 1000 (115 V)	170 9971 5034	1000	1015	30 (50)	25	3.46 (88)	5.24 (133)	5.59 (142)	1.6 (.74)
PFH-T 1000 (230 V)	170 9971 0034	1000	1015	30 (50)	25	3.46 (88)	5.24 (133)	5.59 (142)	1.6 (.74)
PFH-T 1200 (230 V)	170 9981 0034	1200	1215	30 (50)	31	3.46 (88)	5.24 (133)	5.59 (142)	1.6 (.74)

*Heating performance (Ta = +68 °F/+20 °C)

INDUSTRIES & APPLICATION EXAMPLES



Self-service Kiosks



Irrigation & Outdoor Pump Control Systems



Surveillance and CCTV Systems



Telecommunication Systems



Traffic Control Systems



ATMs



Rooftop Control Systems



Parking Control Enclosures



Pfannenberg Incorporated
68 Ward Road, Lancaster, New York 14086 USA
Phone: 716-685-6866 Fax: 716-681-1521

orders@pfannenbergusa.com
www.pfannenbergusa.com

Contact Your Local Representative:

RAMCO INNOVATIONS

1207 Maple St
West Des Moines, IA 50265

www.ramcoi.com

800.328.6236

Subject to technical amendments and misprints.