


Hybrid Module for EtherNet/IP and CIP-Safety

Safe Digital Inputs and Outputs, Standard Universal Digital Channels, IO-Link Master Ports

TBIP-L4-FDIO1-2IOL



- EtherNet/IP™
- Integrated Ethernet switch
- 10 Mbps / 100 Mbps supported
- 2 x male M12, 4-pin, D-coded, Ethernet-Fieldbus connection
- Glass fiber reinforced housing
- Shock and vibration tested
- Fully potted module electronics
- Protection classes IP65, IP67, IP69K
- 7/8" connector for power supply, 4-pin
- Two safe digital SIL3-inputs
- 2 safe digital SIL3 channels as FDI or FDO (PP, PM)
- 4 non-safe digital I/O channels
- 2 IO-Link Master V1.1 slots

Type designation

TBIP-L4-FDIO1-2IOL
100000360

Supply

Supply voltage	24 VDC
Admissible range	20.4...28.8 VDC
Voltage supply connection	4-pin male 7/8" connector X1
Electrical isolation	galvanic isolation of the voltage groups V1 and V2, voltages up to 500 VAC

System data

Fieldbus transmission rate	10 Mbps/100 Mbps
Fieldbus connection technology	2 x M12, 4-pin, D-coded
Web server	integrated
Service interface	Ethernet via P1 or P2

EtherNet/IP™

Addressing	acc. to EtherNet/IP™ specification
Quick Connect (QC)	< 150 ms
Device Level Ring (DLR)	supported
Class 1 connections	3

Safety Data

PL acc. to DIN EN 13849-1:2008	e
Category acc. to DIN EN 13849-1:2008	4
SIL according IEC 61508	3
Useful Lifetime	20 Jahre (EN ISO 13849-1)

Safety Inputs OSSD

Low level signal voltage	EN 61131-2 Type 1 (< 5 V; < 0.5 mA)
High level signal voltage	EN 61131-2 Type 1 (> 15 V; > 2 mA)
Max. OSSD supply per channel	2 A per C0, C1, C2, C3, 1.5 A at 70 °C Please consider derating as shown in figure 1
Max. tolerance test pulse width	1 ms
Interval between 2 test pulses, minimum	20 ms at 1 ms test pulse width 15 ms at 0.5 ms test pulse width

Safety Inputs floating/antivalent

Max. loop resistance	< 150 Ω
Max. cable length	max. 1 µF at 150 Ω Limited by line capacity
Test pulse, typical	0.6 ms
Test pulse, maximum	0.8 ms
Sensor supply	Power supply V AUX1/T1 max. 2 A Please consider derating as shown in figure 1
Interval between 2 test pulses, minimum	900 ms
Additional information	No connection to external potential allowed

Figure 1





Figure 2



Hybrid Module for EtherNet/IP and CIP-Safety

Safe Digital Inputs and Outputs, Standard Universal Digital Channels, IO-Link Master Ports

TBIP-L4-FDIO1-2IOL

Safety Outputs

Output current in off state	< 5 V
Output current in off state	< 1 mA
	suitable for inputs according to EN 61131-2 Type 1
Test pulse, typical	0.5 ms
Test pulse, maximum	1.25 ms
Interval between 2 test pulses, typical	500 ms
Interval between 2 test pulses, minimum	250 ms
Actuator power supply	Power supply V AUX1/T1 max. 2 A
	Please consider derating as shown in figure 1
Max. output current	2 A (resistive)
	1 A (inductive)
Additional information	The load must be mechanically or electrically inert to tolerate the test pulses.
	When configured as a PPM switching output the negative pole of the load should be wired to the M-terminal of the corresponding output (Pin 2).

Digital inputs

Connectivity inputs	M12, 5-pin
Input type	PNP
Switching threshold	EN 61131-2 Typ 3, PNP
Low level signal voltage	< 5 V
High level signal voltage	> 11 V
Low level signal current	< 1.5 mA
High level signal current	> 2 mA
Input delay	2.5 ms
Sensor supply	C4, C5: FSO 0 max. 2 A; 500 mA per input
	C6: V AUX1 max. 2 A
	C7: FSO1 max. 2 A
	Please consider derating as shown in figure 1
Electrical isolation	galvanic isolation to P1/P2
	, voltages up to 500 VDC

Digital outputs

Connectivity outputs	M12, 5-pin
Output type	PNP
Type of output diagnostics	Channel diagnostics
Output voltage	24 VDC from potential group
Output current per channel	0.5 A, short-circuit proof,
	max. 2 A (resistive)/ 1 A (inductive) all std. outputs
Short-circuit protection	yes
Actuator power supply	C4, C5: FSO 0 max. 2 A; 500 mA per output
	C6: V AUX1 max. 2 A
	C7: FSO1 max. 2 A
	Please consider derating as shown in figure 1
Electrical isolation	galvanic isolation to P1/P2
	, voltages up to 500 VDC

IO-Link

Number of channels	2
IO-Link specification	Version 1.1
IO-Link port type	Class A and Class B
Frame type	supports all specified frame types
Supported devices	max. 32 byte input/32 byte output
Transmission rate	4.8 kbps (COM 1) / 38.4 kbps (COM 2) / 230 kbps (COM 3)
Power supply	Power supply V AUX1 max. 2 A
	Please consider derating as shown in figure 1

Standard/Directive conformity

Vibration test	acceleration to 20 g
	acc. to EN 60068-2-6
Shock test	acc. to EN 60068-2-27
Drop and topple	acc. to EN 60068-2-31/IEC 60068-2-32
Electromagnetic compatibility	acc. to EN 61131-2

Hybrid Module for EtherNet/IP and CIP-Safety

Safe Digital Inputs and Outputs, Standard Universal Digital Channels, IO-Link Master Ports


TBIP-L4-FDIO1-2IOL

General Information

Dimensions (W x L x H)	60.4 x 230.4 x 39mm
Operating temperature	-40...+70 °C
Storage temperature	-40...+85 °C
Altitude	max. 5000 m
Protection class	IP65 IP67 IP69K
Housing material	PA6-GF30
Housing color	Black
Window material	Lexan
Material screw	303 stainless steel
Material label	Polycarbonate
Halogen-free	yes
Mounting	2 mounting holes □ 6.3 mm

The data sheet serves as advance information. For definitive values see the corresponding product manual. In this respect, no liability for completeness and accuracy can be applied to the content of this data sheet.




Hybrid Module for EtherNet/IP and CIP-Safety
Safe Digital Inputs and Outputs, Standard Universal Digital Channels, IO-Link
Master Ports
TBIP-L4-FDIO1-2IOL



Accessories

Ethernet cable (example):
 RSSD RSSD 441-2M
 Ident no. U-02482



M12 × 1 Ethernet



Accessories

Actuator and sensor cable/PUR connection cable (example):
 RKC4.5T-2-RSC4.5T/TXY
 Ident. no. 6629805



M12 × 1 Safety Inputs



Accessories

Actuator and sensor cable/PUR connection cable (example):
 RKC4.5T-2-RSC4.5T/TXY
 Ident. no. 6629805



M12 × 1 Safety I/O Port



Accessories

Actuator and sensor cable/PUR connection cable (example):
 RKC4.5T-2-RSC4.5T/TXL
 Ident. no. 6625612


M12 × 1 I/O Port



Accessories

Actuator and sensor cable/PUR connection cable (example):
 Connection of a class A device:
 RKC4T-2-RSC4T/TXL
 Ident. no. 6625604
 Connection of a class B device:
 RKC4.5T-2-RSC4.5T/TXL
 Ident. no. 6625612


M12 × 1 IO-Link



Hybrid Module for EtherNet/IP and CIP-Safety



Safe Digital Inputs and Outputs, Standard Universal Digital Channels, IO-Link
Master Ports

TBIP-L4-FDIO1-2IOL




Accessories
Actuator and sensor cable/PUR connection cable (example):
Connection of a class A device:
RKC4T-2-RSC4T/TXL
Ident. no. 6625604
Connection of a class B device:
RKC4.5T-2-RSC4.5T/TXL
Ident. no. 6625612

M12 × 1 IO-Link



Accessories
Power supply cable (example):
RSM RKM 40-2M
Ident no. U2280-0

7/8" Power Supply



Hybrid Module for EtherNet/IP and CIP-Safety

Safe Digital Inputs and Outputs, Standard Universal Digital Channels, IO-Link Master Ports

TBIP-L4-FDIO1-2IOL



Module LED Status

LED	Color	Status	Description
ETH1/ETH2	Green	ON	Ethernet Link (100 Mbps)
		flashing	Ethernet communication (100 Mbps)
		OFF	No Ethernet link
BUS	Green	ON	Active connection to a master
		flashing	Ready
	Red	ON	IP-address conflict or Restore Mode or Modbus timeout
		flashing	Blink/Wink command active
	Red/Green	alternating	Autonegotiation or waiting for DHCP/Boot-P addressing
ERR	Green	ON	Diagnostics disabled
	Red	ON	Diagnostics enabled
PWR	Green	ON	Power supply V _I OK
		OFF	V _I power off or below defined tolerance of 18 V

LED Status I/O

LED	Color	Status	Description
0...3	Green	ON	Channel active
		flashing	Self test
	Red	ON	Discrepancy
		flashing	Cross circuit
4...7	Green	ON	Channel active
		flashing	Self test (input only)
	Red	ON	Discrepancy, overload (output only)
		flashing	Cross circuit
8...11	Green	ON	Channel active
	Red	ON	Overload (output only)
		flashing	Overload of supply
	Green/Red	alternating	Channel active and overload of supply (input only)
12, 14 (IO-Link Port 1 and 2) IO-Link Mode	Green	flashing	IO-Link communication, process data valid
	Red	flashing	IO-Link communication, process data invalid
		ON	IO-Link supply OK, no IO-Link Communication
		OFF	Port inactive
12, 14 (IO-Link Port 1 and 2) SIO Mode	Green	ON	Digital Input signal is present
		OFF	No input signal
13, 15	Green	ON	Digital input or output active
		Red	Output active with overload/short circuit
	Red	flashing	Overload of supply
		OFF	Input or output inactive

Hybrid Module for EtherNet/IP and CIP-Safety
Safe Digital Inputs and Outputs, Standard Universal Digital Channels, IO-Link
Master Ports
TBIP-L4-FDIO1-2IOL



Process Data Mapping of the Single Protocols

For more details on the corresponding protocols see manual.